

**3 3/8" Product Line**

**Casing Collar Locator**

The Casing Collar Locator is run in cased holes and records the depth of the casing and tubing collars. It is mainly used together with an acoustic device when running a cemented bond log (CBL).

| Specifications      |         |              |   |
|---------------------|---------|--------------|---|
| Diameter:           | 86 mm   | (3.39")      | Sensor Type: Electromagnetic Coil Array |
| Length:             | 1278 mm | (50.3")      |   |
| Weight:             | 43 kg   | (95 lbs)     |   |
| Max. Temp:          | 175°C   | (350°F)      | Measure Point: 582 mm (22.9")           |
| Max. Pressure:      | 140 MPa | (20 000 psi) |   |
| Telemetry required: | yes     |              |   |
| Top Connector:      | yes     |              |   |
| Bottom Connector:   | yes     |              |   |

| Measuring Parameters: |  |
|-----------------------|--|
| Measuring Range:      | 100 to 500 mm (3.9 to 19.7")<br>single casing string |
| Accuracy:             | NA   |

| Logging Parameters          |                                    |
|-----------------------------|------------------------------------|
| Recommended Min. Casing ID: | 106 mm (4.2")                      |
| Recommended Max. Casing ID: | 500 mm (19.7")                     |
| Recommended Logging Speed:  | up to 30 m/min<br>up to 5900 ft/hr |

| Displayed Standard Curves |                       |
|---------------------------|-----------------------|
| CCL in mV                 | Casing Collar Locator |

**Combinability**  
With all other 3 3/8" instruments

